

1                                    TITLE OF THE INVENTION

2            **Method and System for Routing Packets over Parallel Links Between**  
3                                    **Neighbor Nodes**

4                                    BACKGROUND OF THE INVENTION

5                                    Field of the Invention

6            The present invention relates generally to routing of packets in a  
7            communications network and more specifically to routing of packets in an IP  
8            (Internet Protocol) network where a plurality of parallel transmission links  
9            are provided between neighbor routers (nodes).

10                                  Description of the Related Art

11            The amount of traffic in the IP network is doubled every four to eight  
12            months. In order to carry this increasing IP traffic, the routers introduced to  
13            the North American backbone IP network have an increased capacity and an  
14            increased speed to such an extent that the speed of line interface is  
15            approaching its limit comparable to the level of OC-192 (10 Gbps). Owing to  
16            the recent advance in wavelength division multiplexing (WDM) technology,  
17            however, the number of logical links between routers is expected to increase  
18            further.

19            In the IP backbone network, routing tables are created and  
20            autonomously updated by individual routers by reporting their current  
21            status with neighbor nodes according to the routing protocol, which is  
22            classified into the link state protocol and the distant vector protocol. In the  
23            backbone network of internet service providers, the link state type such as  
24            OSPF (Open Shortest Path First) and IS-IS (Intermediate System to  
25            Intermediate System) is employed. According to the link-state routing

1 algorithm, neighbor routers exchange hello packets to identify their  
2 neighbors. In a subsequent learning process, known as flooding, each router  
3 transmits an LSA (link state advertisement) packet to all of its neighbors to  
4 advertise all of their status information and receives an LSA packet from each  
5 of its neighbors and retransmits it to every other neighbor. In this learning  
6 process, flooding is repeated so that each router in a given area creates a  
7 database of its relationships with all neighbor routers of the area. Once a  
8 database is created, the router proceeds to calculate a shortest path first (SPF)  
9 tree using the router itself as the root of the tree with shortest paths to remote  
10 routers, and creates a routing table based on the SPF tree. According to the  
11 link-state routing protocol, the Dijkstra algorithm is employed to calculate the  
12 SPF tree. The performance of Dijkstra algorithm scales as  $O((n + L) \times \log(n))$ ,  
13 where  $L$  is the number of links in the network area of interest and  $n$  is the  
14 number of routers in that area.

15 However, since the LSA packet produced by a given router contains  
16 the status information of all outbound links of the router, the amount of link  
17 state information contained in the LSA packet increases significantly with an  
18 increase in the number of parallel links between neighbor routers. Further,  
19 each router transmits LSA packets on all of its parallel links. Therefore, the  
20 amount of routing control traffic increases in proportion to the square of the  
21 number of parallel links. In addition, since the SPF tree computations  
22 increase in proportion to the total number of links within the network area of  
23 interest, the increase in parallel links results in a significant increase in the  
24 amount of SPF tree computations.

25 A further problem is that if the link metric is inversely proportional to

1 the link bandwidth, an appropriate route is not selected in the SPF tree  
2 calculation. For example, if routers A and B are connected by twenty links of  
3 100 Mbps each and routers A and C are connected by a single link of 600  
4 Mbps, the single A-C link will be selected preferentially over the A-B links  
5 due to the smaller value metric of the A-C link although the total bandwidth  
6 of the A-B links is greater. Although this problem could be solved by setting  
7 the total bandwidth of the A-B links as 2 Gbps, a link failure would affect the  
8 amount of available resource and the set value of total bandwidth does not  
9 represent the actual situation.

#### 10 SUMMARY OF THE INVENTION

11 It is therefore an object of the present invention to provide a method  
12 and system for routing packets in a network where routers are interconnected  
13 by parallel links by ensuring network scalability and stability while using the  
14 conventional link state routing algorithm.

15 The stated object is obtained by having the link state routing algorithm  
16 treat a plurality of parallel links as a single, bundled link, rather than as  
17 individual, component links.

18 According to a first aspect of the present invention, there is provided a  
19 method of routing packets in a communications network, wherein the  
20 network comprises a plurality of nodes which are interconnected by parallel  
21 component links, the method comprising the steps of grouping the parallel  
22 component links into a bundled link, and performing routing calculations  
23 according to a link state routing algorithm on using the bundled link as a unit  
24 of transmission medium.

25 According to a second aspect, the present invention provides a routing

1 controller for routing packets in a communications network, wherein the  
2 network comprises a plurality of nodes which are interconnected by parallel  
3 component links. The routing controller comprises a link manager for  
4 grouping the parallel component links into a bundled link, and a routing  
5 module for performing routing calculations according to a link state routing  
6 algorithm using the bundled link as a unit of transmission medium.

7 For grouping and routing purposes, a first database is created for  
8 mapping a plurality of bundled links to a plurality of component links and a  
9 second database is created for mapping a plurality of destination addresses to  
10 a plurality of bundled links.

11 According to a third aspect, the present invention provides a router for  
12 routing packets in a communications network, wherein the network  
13 comprises a plurality of routers which are interconnected by parallel  
14 component links. The router comprises a routing controller, a plurality of  
15 interface units connected to the parallel component links, and a switch for  
16 switching an inbound hello packet from the interface units to the link  
17 manager and switching an outbound hello packet from the link manager to  
18 the interface units and switching a data packet between the interface units.  
19 The routing controller is arranged to group the parallel component links into  
20 a bundled link according to a link-up or link-down request and produces a  
21 first database and perform routing calculations according to a link state  
22 routing algorithm using the bundled link as a unit of transmission medium  
23 and produces a second database. The first and second databases are used in  
24 each interface unit for translating the header of the data packet.

25 To establish a reserved path through the network, the routing

1 controller transmits a signaling packet containing a transfer list of nodes to a  
2 downstream neighbor node if the bundled link to this node has an idle  
3 component links. When the routing controller of the neighbor node receives  
4 the signaling packet, it sets up a connection in a matrix table according to the  
5 transfer list of the received packet if the bundled link to the next neighbor  
6 node has an idle component link.

7 One feature of the present invention is that the traffic of control  
8 packets exchanged between routers is reduced by treating parallel  
9 component links as a single bundled link even if there is a request for change  
10 in the number of component links if that change is insignificant for carrying  
11 data traffic.

12 Another feature of the present invention is that the time necessary for  
13 routing calculations is reduced even if there is a request for change in the  
14 number of component links if that change is insignificant for carrying data  
15 traffic.

16 Another feature of the present invention is that high speed table  
17 updating is possible in the event of a link failure by the provision of first and  
18 second databases, where the first database is one that is updated at low speed  
19 according to routing protocol and maps destination addresses to bundled  
20 links and the second database is one that can be updated at high speed and  
21 provides mapping of each bundled link to its component links.

22 A still further feature of the present invention is that the need for pre-  
23 setting IP interface address of a neighbor router is eliminated by exchanging  
24 hello packets on individual (component) links, containing IP interface  
25 addresses of bundled links.

1 A still further feature of the present invention is that the  
2 communications network provides scalable routing without requiring  
3 increase in memory, CPU processing burden and control traffic even though  
4 parallel links between neighbors are increased.

#### 5 BRIEF DESCRIPTION OF THE DRAWINGS

6 The present invention will be described in detail further with reference  
7 to the following drawings, in which:

8 Fig. 1 is a block diagram of a communications network comprising  
9 routers interconnected by parallel component links which are grouped into  
10 bundled links;

11 Fig. 2 is a block diagram of a router of Fig. 1;

12 Fig. 3 is a block diagram of a routing module of the router;

13 Fig. 4 shows a component link (CL) management table used in the  
14 routing module for holding learned database created by exchanging hello  
15 packets over component links;

16 Fig. 5 is a flowchart of the operation of a component link (CL) manager  
17 of the routing module to perform hello packet exchanging with neighbor  
18 routers;

19 Fig. 6 is a sequence diagram for explaining a sequence of hello packets  
20 exchanged between two neighbor routers;

21 Fig. 7 shows a bundled link (BL) management table used in the routing  
22 module for holding information associated with bundled links when they are  
23 grouped according to routers;

24 Fig. 8 shows a BL-to-CL mapping table associated with the bundled  
25 link manager;

1        Fig. 9 is a flowchart of the operation of the bundled link (BL) manager  
2        to perform bundling of component links and reporting to a link-state routing  
3        controller when an event occurs in link topology;

4        Fig. 10 is a block diagram of each interface unit of Fig. 2;

5        Fig. 11 shows a modified BL management table for holding  
6        information associated with bundled links when they are grouped according  
7        to bandwidths;

8        Fig. 12 shows how the interface IP address of the BL management table  
9        of Fig. 11 is updated in a learning process;

10       Fig. 13 is a block diagram of a communications network comprising a  
11       plurality of routers interconnected by a network of optical cross-connect  
12       (routers) nodes;

13       Fig. 14 is a block diagram of the network of Fig. 13 in which the  
14       component optical links are grouped into bundled optical links, illustrating a  
15       wavelength path established through the cross-connect nodes;

16       Fig. 15 shows a CL management table provided in the cross-connect  
17       nodes;

18       Fig. 16 shows a BL management table provided in the routers of Fig.  
19       13;

20       Fig. 17 is a flowchart of the operation of an optical cross-connect node  
21       when a matrix table is set for reserving network resource of a wavelength  
22       path; and

23       Figs. 18A and 18B are schematic diagrams illustrating part of the  
24       network of Fig. 13 to explain how a signaling packet is sent from a source  
25       router to a neighbor cross-connect node and then relayed to the next cross-

1 connect node.

2 DETAILED DESCRIPTION

3 Referring to Fig. 1, there is shown an exemplary communications  
4 network of the present invention. The network is comprised of a plurality of  
5 interconnected routers 51 ~ 56. At least one communication link is used to  
6 interconnect neighbor routers of the network. In the illustrated example, the  
7 router 51 is interconnected with the neighbor router 52 by parallel links 101 ~  
8 104 and further interconnected by parallel links 105 ~ 108 with the neighbor  
9 router 54. Each router is uniquely identified by an IP address, or a router  
10 identifier RID.

11 In the present invention, communication links may be either physical  
12 transmission mediums or virtual connections established in an ATM  
13 network. The links having a common attribute are grouped into a "bundled  
14 link (BL)" and the links that constitute a bundled link are termed "component  
15 links (CL)". In the network, each bundled link is locally identified by a  
16 bundled link identifier BLID and each component link is locally assigned a  
17 component link identifier CLID. The BLID of a bundled link is globally  
18 represented by a concatenation of an interface IP address of the bundled link  
19 at the local end and a corresponding interface IP address of the link at the  
20 distant end.

21 According to one embodiment of the present invention, the parallel  
22 links that interconnect two neighboring routers of the same router identifiers  
23 are grouped into a bundled link. For example, the links 101 ~ 104  
24 interconnecting the routers 51 and 52 are grouped into a bundled link 110  
25 and the links 105 ~ 108 interconnecting the routers 51 and 54 are grouped into



1 a bundled link 111. The grouping of interconnecting links into bundled links  
2 allows implementation of scalable routing control over the communication  
3 network of Fig. 1.

4 One router of the network of Fig. 1 is represented by numeral 1 in Fig.  
5 2. The router 1 includes a routing controller 2, a switch 3 and a first group of  
6 interface units 4a ~ 4d connected between the switch 3 and component links  
7 10a ~ 10d and a second group of interface units 4e ~ 4h connected between  
8 the switch 3 and component links 10e ~ 10h.

9 An inbound control packet, which is produced by the respective  
10 routing module of the neighbor routers, is received by one of the interface  
11 units 4 and routed through the switch 3 to the routing controller 2. In  
12 response, the routing controller 2 formulates and transmits an outbound  
13 control packet through the switch 3 to the interface unit where the inbound  
14 packet was received for transmission to the sending router. In this way, the  
15 routing controller 2 exchanges control packets with each of the neighbor  
16 routers on all parallel component links. Based on link state information and  
17 bundled link information contained in all inbound control packets, the  
18 routing controller 2 creates routing (mapping) tables and downloads them to  
19 all interface units 4a ~ 4h.

20 The routing table downloaded to each interface unit is examined when  
21 an inbound data packet is received from a neighbor router and the header of  
22 the data packet is translated according to the downloaded tables and  
23 launched into the switch 3. Switch 3 uses the header information of the  
24 packet for routing it to an appropriate interface unit for transmission.

25 As shown in detail in Fig. 3, the routing controller 2 is comprised of a

1 parallel link manager 20 which bundles component links having same  
2 attributes into a bundled link. A link state routing module 26 of the type  
3 known in the art is connected to the parallel link manager 20 to perform  
4 routing control on a per bundled link basis using information supplied from  
5 the parallel link manager 20, rather than on a per component link basis, by  
6 treating bundled links communicated from the BL manager 22 in the same  
7 way as the conventional routing module does. Thus, the routing controller  
8 performs routing calculations according to the link state routing algorithm  
9 using the bundled link as a network resource unit. Specifically, the processor  
10 26 provides mapping of a plurality of destination addresses to a plurality of  
11 bundled links in an address-to-BL mapping table 28. The contents of the  
12 address-to-BL mapping table 28 are downloaded to all interface units 4a ~ 4h.

13 A component link (CL) interface driver 27 is provided for interfacing  
14 the parallel link manager 20 with the switch 3 to all control packets to be  
15 exchanged with all interface units 4a ~ 4h.

16 Parallel link manager 20 includes a link manager 21, a bundled link  
17 manager 22, and an interface converter 23. BL manager 22 and the bundled  
18 link- component link (BL-CL) converter 23 are associated with a bundled link  
19 management table 25. The bundled link manager 22 is connected to a BL-to-  
20 CL mapping table 29 for mapping a plurality of bundled links to a plurality  
21 of component links and informs the routing module 26 of the identifier of a  
22 bundled link it has determined in a manner as will be described. The  
23 contents of the BL-to-CL mapping table 29 are also downloaded to all  
24 interface units 4a ~ 4h.

25 The BL-CL converter 23 receives LSA packets from the routing module

26 as well as from the individual links 10 via the interface driver 27. In response to an LSA packet from the processor 26, the BL-CL converter 23 examines the BL management table 25 and selects a link from a bundled link that is specified by the LSA packet and hands it over to the interface driver 27 for transmission on the selected link. On the other hand, if an LSA packet is received from a given link 10 via the interface driver 27, the BL-CL converter 23 examines the BL management table 25 and hands it over to the routing module 26, indicating that an LSP packet has arrived on a bundled link of which the given link forms a part.

The CL manager 21 exchanges hello packets with neighbor routers through individual links 10. The hello packet contains a sending router identifier (SRID) which identifies the router that is transmitting a hello packet, a sending interface identifier (SIID) which is set equal to the IP address of the interface transmitting the hello packet, a neighbor router identifier (NRID) that identifies the neighbor router through which the hello packet is received, and a hello packet holding time (HHT) that specifies a time interval to indicate that if no hello packet is received between two neighbor routers during this interval the relationship between these neighbor routers is discarded.

The CL manager 21 is associated with a component link management table 24. As shown in Fig. 4, the CL management table 24 has a plurality of entries corresponding to the component links 10a to 10h, identified by component link identifiers CLID=1 through CLID=10. Each entry is divided into fields 24-1 ~ 24-4 for setting a component link state (CLST), a neighbor router identifier (NRID), a neighbor router component link identifier

(NCLID) and a link bandwidth (LBW), respectively. The CL state field 24-1 is initially set equal to DOWN state. When a neighbor relationship is established on a component link, the CL state field 24-1 of the corresponding entry is set equal to an ESTABLISHED state. If the CL manager 21 is informed that its lower layer is requesting a LINK-UP (or LINK-DOWN) state during the time a neighbor relationship is still not established, the CL state field 24-1 is set to an UP (or DOWN) state.

The CL manager 21 operates with the CL management table 24 according to the flowchart of Fig. 5.

When a hello packet is received from a neighbor router (step 501), the CL manager 21 starts a timer to start a hello timing operation (step 511), updates the CL management table 24 with the identifiers contained in the received hello packet (step 512), and checks to see if the neighbor router identifier (NRID) of the packet matches the identifier of its own router 1 (step 513). If the hello packet is the first one the router 1 receives from the sending neighbor router, the NRID field of the packet contains no identifier. Thus, the decision is negative at step 513 and steps 509 and 510 are repeated to change the CLST field to up-state and send back a reply hello packet to the sending router by setting the NRID field of the hello packet to the identifier of the neighbor router.

In a learning process, steps 501, 511 to 513, 509 and 510 or steps 501, 511 to 517 are repeated to create a database in the CL management table 24.

If the decision at step 513 is affirmative, the CL manager 21 proceeds to step 514 to set an "ESTABLISHED" state in the CL state field 24-1 of the entry corresponding to the component link on which the hello packet was received.

1 If the router 1 is the one that initiated the exchanging of hello packets, the CL  
2 manager 21 makes an affirmative decision at step 515 and proceeds to step  
3 516 to return a hello packet to the neighbor node by setting the SLID and  
4 NRID fields of the packet with the identifiers of the local router and the  
5 neighbor router, respectively. At step 517, the CL manager 21 sends a link-up  
6 request to the BL manager 22 containing the neighbor router ID and the  
7 bandwidth of the component link. If the router is not the initiator of hello  
8 packet exchange, the decision at step 515 is negative and flow proceeds to  
9 step 517, skipping step 516.

10 If no hello packet is received from a neighbor router, the CL manager  
11 21 proceeds from step 501 to step 502 to check to see if a link-down request  
12 for a component link is received from its lower layer. If so, the CL state field  
13 24-1 of the entry corresponding to the requested component link is set to  
14 DOWN state (step 507) and the NRID field 24-2 and NRLID field 24-3 of the  
15 entry are cleared. At step 508, the CL manager 21 sends a link-down request  
16 to the BL manager 22 containing the neighbor router ID, the local and  
17 neighbor interface IP addresses and the bandwidth of the component link if  
18 neighbor relationship was established before the CLST field is updated to  
19 down-state at step 507.

20 If no link-down request is received from the lower layer at step 502,  
21 the CL manager 21 checks, at step 503, to see if a link-up request for a link is  
22 received from the lower layer. If so, flow proceeds to step 509 to set the list  
23 state field 24-1 of an entry corresponding to the requested link and reads the  
24 NRLID and NRID of the entry. The CL manager 21 formulates a hello packet  
25 with the read identifiers and transmits it over a link requested by the lower

1 layer (step 510).

2 If no link-up request is received at step 503, the link manager 21  
3 proceeds to step 504 to check the hello timer, if neighbor relationship is  
4 established, to see if it is still running or timed out. If the timer is still  
5 running, control returns to the starting point of the routine. If the timer has  
6 run out, flow proceeds to step 505 to set the link state field of the link to UP  
7 state, and sends a link-down request to the BL manager 22 (step 506).

8 The CL manager 21 establishes a neighbor relationship between  
9 routers 51 and 52 in a manner as shown in the sequence diagram of Fig. 6 by  
10 assuming that the router 51 is the first to send a hello packet.

11 When the CL manager 21 of router 51 receives a link-up request from  
12 its lower layer (step 503, Fig. 5), it sets the CLST field 24-1 of CL management  
13 table 24 to up-state (step 59) and formulates a hello packet by setting the  
14 SRID (sending router identifier) field of the packet with the identifier of  
15 router 51 and leaving the NRID (neighbor router identifier) field vacant, and  
16 transmits the hello packet to the router 52 (step 510).

17 When the CL manager 21 of router 52 receives the first hello packet  
18 from router 51 (step 501), it starts the hello timer (step 511), updates its  
19 associated CL management table 24 with the identifiers contained in the first  
20 hello packet (step 512), changes the CLST field 24-1 of its associated CL  
21 management table from down- to up-state (steps 513, 509) and returns a  
22 second hello packet by setting its SRID and NRID fields with the identifiers of  
23 routers 52 and 51, respectively (step 510).

24 In response to the second hello packet from router 52 (step 501), the CL  
25 manager 21 of router 51 restarts the hello timer (step 511), updates the CL

1 management table 24 (step 512) and sets the CLST field to ESTABLISHED  
2 state (steps 513, 514). Since the router 51 is the initiator of hello-packet  
3 exchange (step 515), it returns a third hello packet to router 52 by setting its  
4 SRID and NRID fields with the identifiers of routers 51 and 52, respectively  
5 (steps 515, 516) and sends a link-up request to its BL manager 22 containing  
6 the NRID, the local and neighbor interface IP addresses and CLBW (step 517).

7 In response to the third hello packet (501), the CL manager 21 of router  
8 52 restarts the hello timer (step 511), updates its CL management table 24  
9 (step 512) and sets the CLST field to ESTABLISHED state (steps 513, 514) and  
10 sends a link-up state to its BL manager 22 informing the NRID and CLBW  
11 (step 517).

12 When hello packets are exchanged over component links between  
13 neighbors, interface IP addresses are exchanged and a database is created in a  
14 learning process. Thus, network provider is freed from the trouble of  
15 manually pre-setting the bundled link management table of the optical cross-  
16 connect nodes with neighbor interface IP addresses when signaling packet is  
17 used to establish a wavelength path between routers.

18 The BL manager 22 operates with the BL management table 25 to  
19 produce mapping data to be stored in the BL-to-CL mapping table 29. Figs. 7  
20 and 8 show details of these tables. As shown in Fig. 7, the BL management  
21 table 25 has a plurality of entries corresponding to bundled links. For each  
22 bundled link, the corresponding entry is divided into a plurality of fields 25-1  
23 ~ 25-6 for setting a neighbor router identifier (NRID), a bundled link state  
24 (UP or DOWN), the number of component links that comprise the bundled  
25 link, a local interface IP address and a neighbor interface IP address and a

1 total bandwidth, respectively. In the BL-to-CL mapping table 29 defines  
2 relationships between a plurality of bundled links and corresponding  
3 component links as shown in Fig. 8. Since component links are bundled  
4 according to routers, the components links of each bundled link may have  
5 different bandwidths. Therefore, different usage ratios (R) are assigned to the  
6 component links to carry data packets depending on their bandwidths. For  
7 example, a bundled link BLID = 11 is mapped to component links CLID = 1,  
8 CLID = 2 and CLID = 3 and usage ratios R1, R2 and R3 are respectively  
9 assigned to these component links.

10 According to the flowchart of Fig. 9, the operation of the BL manager  
11 22 starts with decision step 901 to determine if a link-up or link-down request  
12 for a component link is received from the CL manager 21.

13 If a link-up request is received, the BL manager 22 makes a search  
14 through the BL management table 25 for an entry that corresponds to the  
15 neighbor router identifier NRID contained in the request (step 902) and  
16 increments the number of component links by one (step 903). At step 904, the  
17 total bandwidth (BLBW) of the bundled link is summed with the bandwidth  
18 (CLBW) of the requested component link.

19 If a link-down request is received at step 901, the BL manager 22  
20 makes a search through the BL management table 25 for an entry that  
21 corresponds to the neighbor router identifier NRID contained in the request  
22 (step 905) and decrements the number of component links by one (step 906)  
23 and subtracts the component link bandwidth from the total bandwidth at  
24 step 907.

25 Following the execution of step 904 or 907, flow proceeds to step 908 to



1 calculate a metric value from the updated total bandwidth of the bundled  
2 link. The BL manager 22 determines whether the number of component links  
3 (CLN) of the bundled link is equal to zero. If  $CLN = 0$ , flow proceeds to step  
4 910 to set the BLST (bundled link state) field 25-2 of the bundled link to  
5 down-state and the BLID of the bundled link is deleted from the BL-CL  
6 mapping table 29 (step 911). At step 912, the BL manager 22 sends a request  
7 to the routing module 26, indicating a link-down state of a BL link and the  
8 updated metric value, requesting the processor to delete the bundled link  
9 from the address-to-BL mapping table 28.

10 If the number of component links (CLN) is not equal to 0 (step 909),  
11 flow proceeds to step 913 to set the BLST field 25-2 of the bundled link to an  
12 up-state and adds a new BLID entry or a new CLID to the BL-CL mapping  
13 table 29 (step 914). At step 915, the BL manager 22 sends a request to the  
14 routing module 26 indicating a BL link-up state and the updated metric value  
15 for requesting the processor to update its table 28.

16 Note that some link-up events may be of such trivial nature that it is  
17 unnecessary to report an altered link topology to the routing module 26. To  
18 this end, an additional routine is preferably provided for checking the status  
19 of each component link at intervals to see if there is a change necessary to  
20 alter the contents of a bundled link by comparing link parameters with  
21 threshold values. If one or more link parameters exceed the thresholds, the  
22 BL manager 22 sends a link-up request to the routing module 26 with a  
23 metric value, requesting it to update the address-BL mapping table 28.

24 By the same token, it is advantageous not to report an event to the  
25 routing module 26 even though there is a change in a bundled link regarding

1 the number of its component links. As a result, the amount of link state  
2 information to be exchanged between routers can be held at a minimum even  
3 if there is a change in the number of parallel links between them. This is  
4 implemented by assigning a metric of particular value to each bundled link  
5 independent of the number of its component links and maintaining the  
6 metric value of each bundled link constant even though the number of its  
7 component links has increased or decreased. For this purpose, the flowchart  
8 of Fig. 9 is modified in such a manner that step 908 is removed and steps 912  
9 and 915 are altered not to report the metric value to the routing controller.

10 Fig. 10 shows details of each interface unit 4. Interface unit 4 is  
11 comprised of a bundled link selector 41 and a component link selector 42  
12 connected in series between the associated component link and the switch 3.  
13 Interface unit 4 further includes first and second mapping tables 43 and 44  
14 connected to the address-to-BL mapping table 28 and the BL-to-CL mapping  
15 29, respectively. When the contents of each of the mapping tables 28 and 29  
16 are created or updated, they are downloaded into the first and second  
17 mapping tables 43 and 44.

18 When a data packet arrives on the interface unit from the associated  
19 component link, the BL selector 41 makes a search through the first mapping  
20 table 43 for the same address as the destination address contained in the  
21 received data packet and reads a bundled link identifier (BLID)  
22 corresponding to the destination address. The read BLID is supplied from  
23 the BL selector 41 to the CL selector 42. Using the BLID from the selector 41  
24 as a search key, the CL selector 42 makes a search through the second  
25 mapping table 44 for the same BLID and reads the corresponding component

1 link identifiers (CLID) and selects one of these CLIDs. The selected CLID is  
2 inserted in the header of the data packet by a header translator 45 and the  
3 packet is sent to the switch 3. According to the translated header, the data  
4 packet is routed through the switch 3 to one of the interface units for  
5 transmission.

6 If one of the component links of a bundled link should fail, the usage  
7 ratios of the bundled link in the BL-CL mapping table 29 are updated so that  
8 the rest of the component links takes the burden of whole traffic of the  
9 bundled link. Since this updating process does not involve the routing  
10 module 26, the present invention compares favorably in terms of processing  
11 speed during a link failure with the prior art in which the routing controller  
12 performs time-consuming recalculations for updating its link-state routing  
13 table.

14 While router identifiers are used in the foregoing description for  
15 bundling parallel links so as to make them appear to the routing module 26  
16 as a single transmission medium, other attributes could equally be as well  
17 employed for bundling parallel links, such as bandwidths, management  
18 groups, link priorities, and light wavelengths of WDM links.

19 If bandwidth is used for bundling component links, the BL  
20 management table 25 may be modified as shown in Fig. 11 in which an  
21 additional field 25-7 is included to set component link bandwidth (CLBW).  
22 In response to a link-up or link-down request from the CL manager 21 for one  
23 of the component links of a bundled link, the BL manager 22 uses the CLBW  
24 field 25-7 of the bundled link for mapping the NRID of the requested  
25 component link in the BL-to-CL mapping table 29 to a BL entry whose CLBW

1 value has the same bandwidth as the requested component link. Since the  
2 component links of the same bandwidth are grouped into the same bundled  
3 link, the usage ratios of BL-to-CL mapping table 29 are all set to an equal  
4 value.

5 As discussed earlier, hello packets are exchanged at intervals to update  
6 the neighbor relationships. In this learning process, the neighbor interface IP  
7 address field of the BL management table 25 is also updated. Therefore, the  
8 neighbor interface IP address field of the modified BL management table 25  
9 can be used to identify each of the component links of a bundled link, where  
10 the component links have the same bandwidth. When an existing neighbor  
11 relationship is updated, the routine of Fig. 9 is invoked and the BL  
12 management table 25 is updated (step 913). One example of this update is  
13 shown in Fig. 12 when a single component link is used to form a bundled link  
14 BLID = 12. This example update changes the BLST field 25-2 to link-up state,  
15 changes the neighbor interface IP address field 25-5 from "unnumbered" to  
16 "133.205.10.3" and sets "1" in the CLN (number of component links) field and  
17 bandwidth values in the bandwidth fields 25-6 and 25-7.

18 It will be seen that the present invention allows the communications  
19 network to provide scalable routing without requiring increase in memory,  
20 CPU processing burden and control traffic even though parallel links  
21 between neighbors are increased.

22 In a communications network where optical cross-connect (routers)  
23 nodes are used to establish relatively static connections between the routers  
24 of the present invention, the routing controller 2 is installed in each of the  
25 cross-connect nodes. One example of such a network is shown in Fig. 13, in

1 which routers 151 ~ 154 of the present invention are interconnected by a  
2 network of optical cross-connect nodes 61 ~ 64, which are interconnected by  
3 wavelength division multiplexers. For example, optical links of cross-connect  
4 nodes 61 and 62 are multiplexed into at least one high-capacity wavelength  
5 path 80 by wavelength division multiplexers 71, and optical links of cross-  
6 connect nodes 63 and 64 may be multiplexed into groups 81 and 82 of high-  
7 capacity wavelength paths by two sets of wavelength division multiplexers  
8 72.

9 Optical cross-connect nodes 61 ~ 64 exchange hello packets with each  
10 other to learn optical link identifiers of neighbor nodes. As shown in Fig. 14,  
11 the routers 151 ~ 154 and cross-connect nodes 61 ~ 64 and forms a group of  
12 parallel optical component links of the same neighbor node identifiers or the  
13 same bandwidth identifiers into a plurality of bundled optical links 201 ~ 206.

14 As shown in Fig. 15, a busy/idle status flag field are additionally  
15 provided in a modified CL management table 24A for indicating busy/idle  
16 status of each component (wavelength) links. As will be described below, the  
17 flags of CL management table 24A are examined by each cross-connect node  
18 for determining whether or not to establish a connection in a matrix table (not  
19 shown) between two component (wavelength) link identifiers (CLIDs) which  
20 identify inbound and outbound wavelength links.

21 Each of the optical cross-connect nodes has a modified BL  
22 management table 25A as shown in Fig. 16. In this table, an additional field is  
23 provided for setting the number of idle component links (ILN) for each  
24 bundled link entry. When a source router sends a signaling packet to  
25 establish a wavelength path to a destination router, it examines the ILN field

1 of the BL management table 25A to determine if there is at least one idle  
2 component link in a bundled link that connects the source router to a  
3 neighbor cross-connect node. Preferably, neighbor routers at the local and  
4 distant end of a component link may use a component link identifier when  
5 transmitting a signaling packet. In this case, the router is not required to  
6 search the CL management table 24A to determine the local CLID.

7 Fig. 17 is a flowchart for setting the matrix table in each optical cross-  
8 connect node in response to a signaling packet originated from a source  
9 router toward a destination router for establishing a wavelength path  
10 between the source and destination routers. Note that the wavelength path is  
11 a series of concatenated wavelength (component) links.

12 The signaling packet contains a CLID identifying a component link on  
13 which it is sent and a "transfer list" of entries which contain source and  
14 destination router identifiers, intermediate node identifiers and an interface  
15 IP address of a bundled link on which the signaling packet is to be sent.  
16 These entries are arranged in transfer order of the signaling packet.

17 When an optical cross-connect node receives a signaling packet (step  
18 1701), it checks to see if the node is specified in the first entry of the packet  
19 (step 1702). If so, the node shifts all entries of the transfer list of the packet to  
20 delete the data contained in its first entry (step 1703). At step 1704, the node  
21 examines the address-BL mapping table 28 to identify an outbound bundled  
22 link corresponding to data now set in the first entry of the transfer list. At  
23 step 1705, the CL management table 24A is referenced to determine whether  
24 its flag field of the identified outbound bundled link contains an idle  
25 component (wavelength) link. If so, flow proceeds to step 1706 to establish a

1 connection in the matrix table between the CLID corresponding to the CLID  
2 contained in the signaling packet and the CLID of the idle component link.  
3 The signaling packet is reformulated with a new CLID identifying the idle  
4 component link of the outbound bundled link and the interface IP address  
5 identifying the bundled link, and then transmitted downstream to the next  
6 node or router specified in the transfer list of the packet (step 1707). If the  
7 decision at step 1705 is negative, a reject message is returned in the upstream  
8 direction (1708).

9 A typical example of signaling packet transmissions will be explained  
10 with reference to Figs. 18A and 18B by assuming that a signaling packet is  
11 sent from the router 151 toward the router 154 via nodes 61, 62 and 64 as  
12 indicated by a broken line 200.

13 Initially, the source router 151 examines the ICN field of the BL  
14 management table 25A to ascertain if the bundled link to the node 61 contains  
15 an idle component link. If there is an idle component, the source router 151  
16 determines that a wavelength path can be established to the router 154 and  
17 formulates a transfer list containing entries for nodes 61, 62, 64 and router 54  
18 arranged in the order named, and makes a search through the CL  
19 management table 24A for an idle component link that forms part of the  
20 bundled link connecting source router 151 to node 61. Router 151 formulates  
21 a signaling packet with the CLID (= 5) of the idle component link and an  
22 interface IP address "133. 206. 40. 2" of the bundled link and sends the packet  
23 to cross-connect node 61.

24 On receiving the packet, the node 61 recognizes that its node identifier  
25 is given in the first entry of the transfer list and shifts all entries to delete the

1 first entry so that the list contains the entries of nodes 62, 64 and router 154  
2 and examines the CL management table 24A. Since the packet contains CLID  
3 = 5 and IP address = 133. 206. 40. 2, the node 61 recognizes that NCLID = 3  
4 corresponds to CLID = 5, determines an outbound bundled link that connects  
5 to the next node 62 and selects a component link of CLID = 5 having an idle  
6 status flag indicated in the CL management table 24A. Node 61 updates its  
7 matrix table by establishing a connection between CLID = 3 on upstream side  
8 of the table and CLID = 5 on downstream side. Finally, the node 61  
9 reformulates the signaling packet with the CLID = 5 of the selected  
10 component link and the IP address "133. 206. 30. 3" of the bundled link that  
11 connects to the next node 62, and transmits the packet to the node 62.

12 The operation of node 62 is similar to that of node 61. In response to  
13 the signaling packet from the node 61, the node 62 recognizes that its node  
14 identifier is found in the first entry of the transfer list and shifts all entries to  
15 delete the first entry so that the list contains the entries of nodes 64 and router  
16 154 and examines the CL management table 24A. Since the packet contains  
17 CLID = 5 and IP address = 133. 206. 30. 3, the node 62 recognizes that NCLID  
18 = 3 corresponds to CLID = 5, determines an outbound bundled link that  
19 connects to the next node 64 and selects a component link having an idle  
20 status flag indicated in the CL management table 24A. Node 62 updates its  
21 matrix table by establishing a connection between CLID = 3 on upstream side  
22 of the table and the CLID of the idle component link on the next downstream  
23 side, and reformulates the signaling packet in a manner similar to that  
24 described above and transmits the packet to the node 64.

25 In this way, the signaling packet is transmitted to the node 64 and a



- 1 wavelength path between routers 151 and 154 is reserved in the matrix tables
- 2 of optical cross-connect nodes 61, 62 and 64.